



CH1 A/R SWR MKR 3: 1.0922 U
 REF 1.000 U 1.000U/ 1 350 000 000.HZ



CH1 START 000 000 000.HZ STOP 3 000 000 000.HZ

MAIN TECHNICAL SPECIFICATIONS

model	Type	
FREQUENCY RANGE		0-3G
INPUT IMPEDANCE		50 OHM
VSWR		1:1.2
GAIN		----
POLARIZATION FORM		----
RADIATION		----
MAXIMUM POWER		----
CABLE		RF1.13-120MM
MAX DIAMETER		13.6mm
MIN DIAMETER		1.13mm
CONNECTOR TYPE		IPEX -- SMAKWE
LIGHTING PROTECTION		DC GROUNDING



SHENZHEN KINGHELM ELECTRONIC CO., LTD.	WWW.BDS666.COM
Model: KH-IPEX-SMAKWE-B180H	0755-83044319

DWN BY/DATE	DESG BY/DATE	TOLERANCE	SCALE		ENG PROJECT NO.	TITLE
CHK BY/DATE	APPD BY/DATE	.X± .XX± .XXX± ANGLES±	1 : 1		150325-0025	IPEX-SMAKWE-RR1.13-180 MM
			UNIT	SH 1 OF 1	CONTROL NO.	DWG NO.
			m / m			REV